



FEATURES:-

- ✓ 13.56 MHz Mifare Card
- ✓ Read range up to 5 cm
- ✓ 34 bit Wiegand (default)
- ✓ Easy to install on Metal Door Frame Mullion.
- ✓ External LED control
- ✓ External buzzer control.
- ✓ Indoor/ Outdoor Operation
- ✓ Solid Epoxy Potted
- ✓ Waterproof
- ✓ Reverse Polarity Protection

ORDER INFORMATION :-



Model : AY-G25 FALCO SMART CARD MIFARE READER



This new, rigid and reliable unit provides the capability to read EM/Mifare® Smartcard Contactless cards with any standard access control system.

The AY-G25 is fully potted, sealed and made of a rigid, UV resistant poly-carbonate, which makes it highly suitable for outdoor use. With a maximum range of 5cm, it makes a very simple, reliable and cost effective way to upgrade your system to Smartcard standard.

SPECIFICATION:-

| | |
|-----------------------|---|
| Model | AY-G25 |
| Read Range | 5cm |
| Reading Time (Card) | ≤300ms |
| Power /Current | DC 6-14V/ Max.70mA |
| Input Port | 2ea (External LED Control, External Buzzer Control) |
| Output Port | 34 bit Wiegand |
| LED Indicator | 2 Colours LED Indicators (Red & Green) |
| Beeper | Yes |
| Operating Temperature | -20 °C to +65°C |
| Operating Humidity | 10% to 90% relative humidity non considered |
| Colour | Black |
| Index of Protection | IP65 |
| Material | ABS+PC with texture |
| Dimensions (mm) | 86(W)x86(H)x16.8(T) |

